Wilcoxon Research

Model 797
Premium, PiezoFET®, low profile IsoRing accelerometer

Dynamic

Sensitivity, ±5%, 25°C	100 mV/g
Acceleration range	50 g peak
Amplitude nonlinearity	1%
Frequency response:	
±5%	3 - 5,000 Hz
±10%	2 - 7,000 Hz
±3 dB	1 - 12,000 Hz
Resonance frequency	26 kHz
Transverse sensitivity, max	5 % of axial
Temperature response:	
–50°C	–5%
+120°C	+5%

Electrical

Power requirement:	voltage source	18 - 30 VDC
	current regulating diode	2 - 10 mA
Electrical noise, equiv. g:		
Broadband	2.5 Hz to 25 kHz	600 µg
Spectral	10 Hz	8 µg/√Hz
	100 Hz	5 µg/√Hz
	1000 Hz	5 µg/√Hz
Output impedance, max.		100 Ω
Bias output voltage		12 VDC
Grounding		case isolated, internally shielded

Environmental

Temperature range	–50 to 120°C
Vibration limit	500 g peak
Shock limit	5,000 g peak
Electromagnetic sensitivity, equiv. g	30 µg/gauss
Sealing	hermetic
Base strain sensitivity	0.002 g/µstrain

Physical

Sensing element design	PZT ceramic / shear
Weight	135 grams
Case material	316L stainless steel
Mounting	1/4-28 captive socket head screw
Output connector	2 pin, MIL-C-5015 style
Mating connector	R6 type
Recommended cabling	J10 / J9T2A

Connector pin	Function	Cable conductor color
Shell	ground	shield
A	power/ signal	white
B	common	black

Features
- Rugged design
- Corrosion resistant
- Hermetic seal
- Ground isolated
- ESD protection
- Reverse wiring protection
- Mounting in any orientation



Accessories supplied: #12105-01captive socket head (metric studs available upon request); calibration data (level 3)
Options: Intrinsic safety certifications

Wilcoxon Research Inc
21 Firstfield Rd
Gaithersburg, MD 20878
USA

Tel: 301 330 8811
Fax: 301 330 8873
Email: sensors@wilcoxon.com

www.meggitt.com

MEGGITT
smart engineering for extreme environments

98244 Rev.C.2 6/99